



Power2Go Mobile Gas Turbine Genset

Mobile gas turbine generator sets offer an undeniable power advantage for oilfield operators, ensuring that critical equipment and processes run smoothly while optimizing operational efficiency.

Power2Go offers impressive power output options between 35 MW or 6 MW. It can generate large amounts of electricity quickly and efficiently, enabling oilfield operators to run a wide range of equipment and machinery simultaneously. This high power capacity translates into increased productivity and faster project completion times.

- **Efficient:** Achieve quick deployment, installation & commissioning through modular design.
- **Safety:** Meet explosion-proof rating of Class I, Division 2 and designed with nearly 200 monitoring points to achieve real-time status monitoring.
- **Convenient:** The exhaust trailer is self-mounted on the main trailer without any lifting device.
- **Eco-friendly:** Run on natural gas to reduce emissions and lower noise level below 90 dBA.

Technical Parameters

Model	Power2Go	Power2Go
	LM2500 +G4 SAC	KB7HE
Genset ISO Power	32.42 MW	5.5 MW
Fuel	Duel Fuel: Diesel or Natural gas (Field gas, CNG or LNG)	
Frequency	60 Hz	50/60 Hz
Efficiency	37.2 %	32.3%
NOx Discharge	≤ 25 ppmv@15% of oxygen content with water injection	≤ 25 ppmv @15% of oxygen content(DLE)
Noise Level	< 90 dBA @ 3.3 ft	< 85 dBA @ 3.3 ft
Terminal Voltage	13.8 kV	10.5/13.8 kV
Max. Output	35 MW	6 MW



Energy Storage System

Jereh is dedicated to providing core equipment of energy storage products, grid integration solution and energy storage solutions of industry and households for global customers. In oil & gas field, Jereh brings microgrid energy storage control system with high customization, various sizes and flexible control modes.

Mobile Energy Storage Product

Items	Specification
Rated Capacity of Electric Core	150 Ah
Voltage Level	900 V
Rated Capacity	2~4 MWh
Rated Frequency	50/60 Hz
Temperature Control	A/C+Forced Air Cooling
Fire Safety	Perfluorohexanone Fire Extinguishing System
C-Rating	1 C
Cycle Life	6,000 +
Temperature Range	-4~131 °F



Distributed Energy Storage Product

Items	Specification	
Composition	1P416S	2P264S
Voltage Range	1,164.8~1,476.8 V	739~937 V
Rated Capacity of Electric Core	280 Ah	120 Ah
Cooling Type	Liquid Cooling	Air Cooling
Rated Power	186 kW	100 kW
Rated Energy	372.7 kWh	202 kWh



JEREH
PRODUCT PROFILE
Index-2022.12-V1/EN

Copyright © Jereh Energy Equipment and Technologies Corporation All rights reserved.

USA Office: 7501 Miller Road 2, Houston, TX 77049

Tel: + 1 281-860-0488

Canada Office: Suite 400, 900 6 Ave SW Calgary AB T2P 3K2

Tel: +1 403-474-1899

E-mail: customerservice@jereh.com www.jereh-eet.com